

SPECIFICATION STANDARD

NAPHTHA LEGER

These specifications are for information purposes only and shall not be binding upon the Seller. The Seller will bear no liability for delivering product that doesn't conform to these specifications.

TEST	UNIT	RANGE	TEST METHOD
Relative Density at 60/60 °F*		0.647 – 0.677	ASTM D4052
API Gravity at 60/60 °F*		77.4 – 78.9	ASTM D4052
Saybolt Color		+30	ASTM D6045
Visual Suspended Free Water & Particulates		PASS	ASTM D4176
Mercaptan Sulfur	mg/kg	65.8 – 550	ASTM D3227
Total Sulfur	mg/kg	73.6 – 550	ASTM D5453
B S & W Centrifuge	% Vol.	0	ASTM D4007
Vapour Pressure at 100 °F	PSI	8.7 – 9.8	ASTM D5191
Distillation: IBP			
10 % Vol.		To be reported	
50 % Vol.			
90 % Vol.			
FBP			
Recovery	% Vol.	97.5 – 99.2	
Residue	% Vol.	0.9	ASTM D86
Loss	% Vol.	0 – 1.6	

The measurement uncertainty are available on request for Relative Density and API Gravity at 60/60 °F *The test is covered by ISO/IEC 17025 accreditation.