



SPÉCIFICATIONS STANDARD

Essence Premium 91 RON (sans plomb)

These specifications are for information purposes only and shall not be binding upon the Seller.
The seller will bear no liability for delivering product/s that doesn't conform to these specifications.

PROPERTY	UNITS	LIMITS	METHOD
Density @ 15°C	kg/m ³	To Be Reported	ASTM D4052
Colour	--	UNDYED	VISUAL
<u>Distillation:</u>			ASTM D86
10 % Volume Recovery	°C	Max 70	
50 % Volume Recovery	°C	Max 118	
90 % Volume Recovery	°C	Max 185	
End Point	°C	Max 225	
R V P @ 100 °F	psi	Max 9.5	ASTM D323
Existent Gum	mg / 100 ml	Max 5	ASTM D381
Research Octane Number	--	Min 91	ASTM D2699
Corrosion Copper Strip, 3 Hrs. @ 50°C	Classification	Max No. 1	ASTM D130
Total Sulphur	PPM Wt.	Max 300	ASTM D5453 / D7039 / D4294
Induction Period @ 100 °C	Minutes	Min 240	ASTM D525
Benzene	LV%	Max 3.0	ASTM D6839 / ASTM D5134
Oxygenate Content – MTBE	Vol%	Max 15	ASTM D4815 / D6839